

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 746 973 A1

(12)

EUROPEAN PATENT APPLICATION

published in accordance with Art. 158(3) EPC

(43) Date of publication:

11.12.1996 Bulletin 1996/50

(51) Int. Cl.⁶: A01G 13/02

(21) Application number: 94907079.1

(86) International application number:
PCT/JP94/00258

(22) Date of filing: 21.02.1994

(87) International publication number:
WO 95/22244 (24.08.1995 Gazette 1995/36)

(84) Designated Contracting States:
DE NL

(71) Applicant: NIPPON CARBIDE KOGYO
KABUSHIKI KAISHA
Tokyo 100 (JP)

• ISHISAKI, Yoshiaki
Ikeda-shi, Osaka 563 (JP)
• OONISHI, Yasuaki
Uozu-shi, Toyama 937 (JP)

(72) Inventors:

• HARASAWA, Isamu
Higashikurume-shi, Tokyo 203 (JP)


(74) Representative: Kraus, Walter, Dr.
Patentanwälte Kraus, Weisert & Partner
Thomas-Wimmer-Ring 15
80539 München (DE)

(54) AGRICULTURAL COVERING MATERIAL

(57) The invention provides an agricultural covering material comprising a fluoro resin film which intercepts at least 40 percent of transmission of ultraviolet rays, having a wavelength in the range of at least 300 to 330 nm, and transmits at least, 70 percent of visible rays in the range of 400 to 800 nm. The present covering mate-

rial can be spread outdoors over a long period of time, and is useful for cultivation of various useful crops as a covering material for use with hothouses to replace glass.

FIG. 1



EP 0 746 973 A1

Description**Technical Field**

The present invention relates to an agricultural covering material, particularly to an agricultural covering material which partially intercepts the rays of particular wavelength ranges and which can be used in a spread state over a long period of time.

Background Art

There have been used, as covering materials for plastic tunnel or pipe house, a polyethylene film, an ethylene-vinyl acetate copolymer film, a polyester film, a vinyl chloride resin film, etc. A vinyl chloride resin film occupies a major portion because of the applicability, price, heat-insulatability, etc. Since these resins have inferior outdoor durability, they are used for 1-2 years and farmers replace the covering materials every 1-2 years.

Full-scale large houses have been used in recent years for the purposes of labor saving for house management, enlargement of cultivation area, cultivation of higher quality crops, prolongation of house life, etc. In these large houses are used, as covering materials durable for about 5 years, such covering materials as polyester resin panel, polycarbonate resin panel, hard vinyl chloride resin panel, acrylic resin panel, fiber-reinforced plastic panel and the like. Since these covering materials have a large thickness, they have drawbacks in that they must use a specially made large base material and be spread, making the application very complicated and moreover they are relatively expensive. A polyester resin panel, a polycarbonate resin panel, a hard vinyl chloride resin panel, an acrylic resin panel, etc. have further problems in that they tend to generate cracks when hit by hail, etc. and the cracks tend to propagate.

Also, flat glass is used as a durable covering material which can be used for 10 years or more. Flat glass, however, has problems in that it is expensive and, moreover, it is broken easily and, once broken, the soil inside house must be replaced to remove the fine pieces of broken glass.

In order to solve these problems, Japanese Patent Application Kokai (Laid-Open) No. 43535/1989, for example, proposes an agricultural covering material comprising a fluororesin film.

While the above-mentioned conventional agricultural covering materials contain a small amount of an ultraviolet absorber for improvement of the weatherability and generally have a property of intercepting the ultraviolet rays of sunlight to some extent, a fluororesin film has excellent weatherability by itself and accordingly requires no use of any weatherability improver (e.g. ultraviolet absorber) therein. Consequently, an agricultural covering material comprising a fluororesin film transmits even the ultraviolet rays of sunlight. Therefore, when the crop for in-house cultivation which had been subjected to breeding so as to fit the cultivation in a house covered with a conventional agricultural covering material capable of intercepting ultraviolet rays to some extent, was cultivated in a house covered with a fluororesin film, there have arisen new problems not experienced with conventional agricultural covering materials, such as delay of growth or harvesting time, reduction in quality of harvest owing to, for example, the hardening of stem and leaf or of fruit, flower color darkening or discoloration of flowers and ornamental plants, and the like.

Fluororesin films are superior in mechanical strengths, transparency, weatherability, etc. and are best suited as a base material for use in an agricultural covering material which can be used in a spread state over a long period of time, for example, 10 years or more. Hence, the present inventors made a study in order to solve the above-mentioned problems possessed by an agricultural covering material comprising a fluororesin film.

It is thought, as one mean for solving the problems, to use an ultraviolet absorber in a fluororesin film as in the case of conventional agricultural covering materials. However, fluororesins have a high melt-processing temperature and it is practically difficult to use therein an organic ultraviolet absorber such as used in conventional agricultural covering materials.

The present inventors have developed a fluororesin film which can be used even for the conventional crops for in-house cultivation without inviting the above-mentioned problems, by using, in a fluororesin, an inorganic fine powder capable of withstanding the melt-processing temperature of fluororesin.

Disclosure of the Invention

According to the present invention there is provided an agricultural covering material comprising a fluororesin film which intercepts the transmission of the ultraviolet rays having a wavelength range of at least 300-330 nm, by at least 40% and which transmits at least 70% of the visible rays having a wavelength range of 400-800 nm.

The fluororesin film used as the agricultural covering material of the present invention intercepts the transmission of the portion of the ultraviolet rays of sunlight, having a wavelength range of at least 300-330 nm, by at least 40%, preferably 60% or more, more preferably 80% or more, most preferably 90% or more. The fluororesin film is not necessarily required to intercept the transmission of the ultraviolet rays having a wavelength longer than 330 nm, but it is desirable that the fluororesin film intercepts as well the transmission of the ultraviolet rays having a wavelength range of about

350 nm or shorter by at least 40%, preferably 50% or more.

Meanwhile, the visible rays having a wavelength range of 400-800 nm, which are necessary for the growth of crops, are desired to be transmitted through the fluororesin film as much as possible. The transmittance of the visible rays through the fluororesin film is at least 70%, preferably 80% or more, more preferably 85% or more, most preferably 88% or more. Herein, "the transmittance of the visible rays having a wavelength range of 400-800 nm" is an average transmittance of the visible rays in said wavelength range.

The fluororesin film having light transmission properties such as mentioned above can be produced, for example, by compounding, into a fluororesin film, an inorganic powder capable of intercepting the transmission of the ultraviolet rays having a wavelength range of at least 300-330 nm, or by forming, on at least one side of a fluororesin film, a coating layer containing the above inorganic powder.

The fluororesin used as a base material in production of the above film is a (co)polymer obtained from a fluorine-containing monomer(s). Specific examples thereof include a polytetrafluoroethylene (PTFE), a tetrafluoroethylene-perfluoroalkylvinyl ether copolymer (PFA), a tetrafluoroethylene-hexafluoropropylene copolymer (FEP), a tetrafluoroethylene-hexafluoropropylene-perfluoroalkylvinyl ether copolymer (EPE), a tetrafluoroethylene-ethylene copolymer (ETFE), a polychlorotrifluoroethylene (PCTFE), a chlorotrifluoroethylene-ethylene copolymer (ECTFE), a polyvinylidene fluoride (PVDF), a polyvinyl fluoride (PVF), and a mixture of at least two of them. Of these, ETFE, PCTFE, ECTFE, PVDF and PVF are preferred; ETFE, PVDF and PVF are more preferred; and ETFE is used particularly preferably.

ETFE is a copolymer of ethylene, tetrafluoroethylene (these two components are major components and the molar ratio of ethylene / tetrafluoroethylene is generally 40 / 60 to 60 / 40) and, as necessary, a small amount (generally 10 mole % or less) of a third comonomer component. In the present invention, there is particularly preferred an ethylene-tetrafluoroethylene type copolymer wherein the molar ratio of ethylene / tetrafluoroethylene is in the range of 40 / 60 to 60 / 40, preferably 45 / 55 to 55 / 45 and wherein the content of a perfluoroalkylvinyl monomer unit represented by a formula $\text{CH}_2=\text{CH}-\text{C}_n\text{F}_{2n+1}$ (n is an integer of 2-10) (for example, a unit derived from $\text{CH}_2=\text{CH}-\text{C}_4\text{F}_9$ or $\text{CH}_2=\text{CH}-\text{C}_6\text{F}_{13}$) is in the range of 0.1-10 mole %, preferably 0.3-5 mole %. This ethylene-tetrafluoroethylene type copolymer is known per se; and it can be produced by, for example, a process described in Japanese Patent Publication No. 50163/1984, or it is commercially available under the brand name of "AFLON COP" (a product of Asahi Glass Co., Ltd.).

Meanwhile, the inorganic fine powder which can be compounded into the fluororesin, can be appropriately selected from oxides, compound oxides, sulfides, carbonates, etc. of metals such as titanium, zirconium, magnesium, calcium, barium, lanthanum, zinc, aluminum, tin, antimony, etc. Specific examples thereof include titanium oxide (TiO_2), zinc oxide (ZnO), mica, alumina (Al_2O_3), colloidal silica (SiO_2), iron oxide (Fe_2O_3), cerium oxide (CeO_2), barium oxide (BaO), antimony oxide (Sb_2O_3), nickel oxide (NiO), chromium oxide (Cr_2O_3), zirconium oxide (ZrO_2), calcium oxide (CaO), tin oxide (SnO_2) and mixtures thereof. Of these, TiO_2 , ZnO , CeO_2 and Fe_2O_3 are preferred, and TiO_2 and ZnO are particularly preferred.

The particle diameters of the inorganic fine powder are not particularly restricted as long as the fluororesin film can be endowed with the above-mentioned optical properties. However, the average particle diameter of the inorganic fine powder is generally 1,000 nm or less, preferably 500 nm or less, more preferably 100 nm or less, particularly preferably 50 nm or less.

The amount of the inorganic fine powder used in the fluororesin film varies depending upon the kind of the resin used and the thickness of the film used, but can be in the range of generally 0.01-10% by weight, preferably 0.1-5% by weight, more preferably 0.3-1% by weight.

The molding of a film from the fluororesin containing the inorganic fine powder can be conducted by a per se known method, for example, extrusion or inflation. The thickness of the film obtained can be generally 10-1,000 μm , preferably 30-200 μm , particularly preferably 50-100 μm .

The fluororesin film having the above-mentioned light transmission properties can be produced also by coating, on the surface of a separately produced fluororesin film having a thickness such as mentioned above, a coating fluid comprising an inorganic fine powder such as mentioned above and a resin binder.

In this case, it is desirable that the surface of the fluororesin film is beforehand subjected to a surface-activating treatment in order to enable the uniform coating of the coating fluid on the surface of the fluororesin film, the tight adhesion of the formed coating layer to the film surface, and so forth.

The surface-activating treatment includes a corona discharge treatment, a sputtering etching treatment, a sodium treatment, a sandblasting treatment, etc.

In the corona discharge treatment, discharge is allowed to take place between a knife edge electrode and an opposing electrode with a sample film placed between the electrodes; as a result, oxygen-containing functional groups such as aldehyde, acid, alcohol peroxide, ketone, ether and the like are formed on the film surface.

In the sodium treatment, the fluororesin film is immersed in a liquid ammonia solution containing an alkali metal such as metallic sodium or the like, whereby the CF_2 bond is allowed to disappear from the film surface and CH and C-O bonds are formed thereon.

In the sputtering etching treatment, a film sample is placed between electrodes which are conducting glow discharge at a low pressure, to allow the positive ions generated by the glow discharge to hit the film to form a large

number of fine projections on the film.

In the sandblasting treatment, a sand of fine particles is blown against a film to form a large number of fine roughnesses on the film surface.

Of these surface-activating treatments, the corona discharge treatment is preferred in view of the adhesivity to the coating layer formed, the workability, the safety, the cost, etc.

The resin binder usable in the coating fluid includes, for example, an acrylic resin, a vinyl acetate resin, a fluororesin and mixtures thereof. It is possible to optionally use, in combination with the resin binder, a hydrophilic polymer, for example, a polyvinyl alcohol, a polyvinylpyrrolidone or a polymer generally having a hydrophilic functional group such as $-SO_4$, $-SO_3H$, $-COOH$, $-CN$, $-(OCH_2CH_2)$ or the like.

The coating fluid may further contain, as necessary, a surfactant such as sorbitan-fatty acid ester, sorbitol-fatty acid ester, diglycerine-fatty acid ester, glycerine-fatty acid ester, sorbitan-fatty acid-dibasic acid ester, sorbitol-fatty acid-dibasic acid ester, diglycerine-fatty acid-dibasic acid ester, glycerine-fatty acid-dibasic acid ester and addition compound obtained by adding an alkylene oxide (e.g. ethylene oxide or propylene oxide) to any of the above esters.

The above-mentioned components are dissolved or dispersed in, for example, water or a solvent of alcohol, ketone, ester or ether type to prepare a coating fluid, and the coating fluid is coated on the fluororesin film. The coating can be conducted by an ordinary method such as brush coating, dip coating, gravure coating, spray coating or the like.

In the coating fluid, the concentration of the inorganic fine powder varies depending upon the thickness of the coating fluid coated, the kind of the resin binder used, etc. However, the content of the inorganic fine powder in the coating layer formed is desirably in the range of generally 0.5-95% by weight, preferably 1-50% by weight, more preferably 3-30% by weight.

The thickness of the coating layer formed is not strictly restricted as long as the resulting film has the above-mentioned light transmission properties, but can be in the range of generally 1-100 μm , preferably 2-50 μm , more preferably 5-20 μm .

The fluororesin film, which can be produced as mentioned above and which has the above-mentioned light transmission properties, shows substantially no change in properties even when used outdoors as an agricultural covering material in a spread state over a long period of time such as 10 years or more, and can be applied to various crops which have been subjected to breeding for in-house cultivation, without causing the above-mentioned problems. Therefore, the fluororesin film can be widely used as a covering material for green house, to replace glass.

According to the present invention, there is also provided a method for cultivation of useful crops, which comprises cultivating useful crops in a greenhouse covered with an agricultural covering material comprising the above-mentioned fluororesin film.

Herein, "useful crops" include agriculture, horticulture and forestry crops useful in human life, and are exemplified by the followings.

[1] Agriculture and horticulture crops

(1) Food crops

Rice, wheat, corn, soybean, sweet potato, potato

(2) Garden crops

Fruit trees

Apple, pear, persimmon, peach, Japanese apricot, grape, loquat, fig, blueberry, pomegranate, lemon, oranges, etc.

Fruit vegetables

Cucumber, watermelon, tomato, strawberry, pumpkin, melon, eggplant, pea, okura, pimento

Root vegetables

Carrot, burdock, taro, ginger, lotus root, wasabi (Japanese horseradish), arrow head, scallion

Leaf vegetables

Chinese cabbage, white stemmed onion, garlic, onion, cabbage, Japanese parsley, spinach, beef steak plant, Japanese butterbur, celery, gynmigh, parsley, trefoil, asparagus, udo salad plant

Flowers (annual and biennial)

Morning glory, cosmos, Iceland poppy aster, yellow sultan, snapdragon, calendula, stock, pansy, sunflower, benidium, dimolphoseca, safflower, white lace flower, cornflower, prairie gentian, lodans

Perennial plants

Lawn grasses, oriental orchid, gypsophila, carnation, gerbera, bellflower, chrysanthemum, rabbit-ear-iris, statice, peony, marguerite

Bulbous plants

Lilies, gladiolus, iris, anemone, calla, daffodil, freesia, ranunculus, blackberry lily

Flowering trees and shrubs

Acasia, azelea, rose, mewsyan, lagerstroemia, winter daphne, chloranthus glaber MAKINO, cyad (Japanese sago palm), camellia, tea oil plant, encalyptus
Greenhouse plants
Orchid, cyclamen

(3) Industrial crops

Oil crops
Rapeseed, sesame
Sugar crops
Sugar cane, sugar beet
Fiber crops
Cotton, hemp, flax, jute
Starch crops
Konjac
Medical herbs
Japanese peppermint, poppy
Recreation crops
Tea, tobacco, hop
Paper-making crops
Paper mulberry, mitsumata
Dye crops
Japanese indigo plant
Flavoring crops
Geranium
Sap crops
Lacquer tree

(4) Forage crops

Forage crops
Orchard grass, red clover, white clover
Plants for feed and manure
Bread tree, silk tree
Green manure crops
Chinese milk vetch, bur clover

[2] Forestry trees

Coniferous trees
Japanese cedar, Japanese cypress, pine tree
Broad leaved evergreens
Aucuba, fatsia
Broad leaved deciduous trees
Nara oak, Siebold's beech

Of these crops, those to which the agricultural covering material of the present invention is applicable particularly favorably, are garden crops; preferably fruit vegetables, root vegetables, leaf vegetables, flowers, perennial plants, flowering trees and shrubs, and greenhouse plants; more preferably fruit vegetables, flowers, perennial plants, and flowering trees and shrubs; most preferably fruit vegetables, and flowering trees and shrubs.

The fruit vegetables to which the present agricultural covering material is applicable favorably, include cucumber, watermelon, tomato, strawberry, melon and pimento, with cucumber, melon and tomato being particularly preferred; the root vegetables are preferably carrot and ginger; and the leaf vegetables are preferably Chinese cabbage, white stemmed onion, celery and trefoil.

The flowers to which the present agricultural covering material is applicable favorably, include stock and prairie gentian; the perennial plants include oriental orchid, gypsophila, carnation, gerbera, chrysanthemum and statice with carnation, gerbera and chrysanthemum being particularly preferred; the bulbous plants are preferably lilies and iris; and the flowering trees and shrubs are preferably rose.

By cultivating these useful crops in a greenhouse covered with the agricultural covering material of the present

invention, there can be obtained various cultivation effects which have not been obtainable with conventional agricultural covering materials, as shown in Examples described later. The effects are summarized as follows.

(1) When the agricultural covering material of the present invention is used, as compared with when conventional covering materials are used, cultivation is very easy. Therefore, farmers do not fail in cultivation and can obtain a stable yield.

(2) When the agricultural covering material of the present invention is used, as compared with when conventional covering materials are used, a harvest of good quality can be obtained in a large amount, and a high profit is promised.

Examples

The present invention is hereinafter described more specifically by way of Examples.

Examples of production of films

Production Example A (a comparative example)

Into an autoclave having an internal volume of 10 liters were fed 3.46 kg of trichloromonofluoromethane, 6.52 kg of trichlorotrifluoroethane and 2.38 g of t-butyl peroxyisobutyrate. Thereto were fed 1,226 g of tetrafluoroethylene, 82 g of ethylene and 26 g of perfluorobutylethylene ($\text{CH}_2=\text{CH}-\text{C}_4\text{F}_9$). The resulting mixture was subjected to a copolymerization reaction with sufficient stirring with the reaction temperature being kept at 65°C.

During the copolymerization reaction, the polymerization pressure was kept at 15.0 kg/cm² by introducing into the system a tetrafluoroethylene / ethylene / perfluorobutylethylene (molar ratio: 53 / 46.3 / 0.7) mixed gas. After 5 hours, 460 g of a white copolymer (hereinafter referred to as resin No. 1) was obtained. The copolymer had a C_2F_4 / C_2H_4 / $\text{CH}_2=\text{CHC}_4\text{F}_9$ molar ratio of 53 / 46.3 / 0.7, a flow-starting temperature of 267°C and a pyrolysis-starting temperature of 360°C.

The above-obtained ethylene-tetrafluoroethylene type copolymer (hereinafter abbreviated to "ETFE" in some cases) was extruded at a resin temperature of 320°C to produce a film No. 1 having a thickness of 60 µm.

Production Example B (a comparative example)

There were mixed 67 parts by weight of a polyvinyl chloride (polymerization degree: 1,300), 25 parts by weight of dioctyl phthalate (a plasticizer), 5 parts by weight of tricresyl phosphate (a plasticizer), 3 parts by weight of an epoxidized soybean oil (a plasticizer), 0.8 part by weight of barium laurate (a stabilizer), 0.5 part by weight of zinc stearate (a stabilizer), 0.3 part by weight of dibutyltin maleate (a stabilizer), 0.6 part by weight of sorbitan monopalmitate (a surfactant) and 5 parts by weight of 2-hydroxy-4'-methoxybenzophenone (a ultraviolet absorber). The resulting mixture was melt-extruded at 200°C by the use of an extruder to obtain a film No. 4 having a thickness of 60 µm.

Production Example C (present invention)

A film No. 2 having a thickness of 60 µm was obtained in the same manner as in Production Example A except that 0.2% by weight of zinc oxide (ZnO) having an average particle diameter of 20 nm was added to the EFTE obtained in Production Example A.

Production Example D (present invention)

One side of the film No. 1 obtained in Production Example A was subjected to a corona discharge treatment under the conditions of discharge current = 10 A, discharge voltage = 120 V and line speed = 13 m/min. Separately, 5% by weight of a polyvinyl alcohol and 5% by weight of TiO_2 having an average particle diameter of 30 nm were added to a silica sol (solid silica content = 8%), and the mixture was diluted 100-fold with ethanol to prepare a coating fluid. The coating fluid was coated on the above-treated side of the film No. 1 in an amount of 15 g/m² to obtain a film No. 3.

Brief Description of the Drawing

Fig. 1 shows the curves of light transmittances at various wavelengths, of the film Nos. 1-4 obtained in the above Production Examples A-D.

Evaluations of film properties

1. Transparency

There were prepared, as conventional agricultural covering materials, a soft vinyl chloride resin film [Noubi Ace (trade name), a product of Mitsubishi Chemical MKV Co., 100 μm], a poly ester film [SIKUSURAITO (trade name), a product of Taiyo Kogyo Co., Ltd., 175 μm], a polycarbonate resin panel [Iupilon (trade name), a product of Mitsubishi Gas Chemical Co., Inc., 1,000 μm] and an acrylic resin panel [Acryl Panel (phonetical translation) (trade name), a product of Mitsubishi Rayon Co., Ltd. 1,700 μm]. These conventional covering materials and the film Nos. 1-4 obtained in the above Production Examples were fixed on an outdoor exposure stand having an inclination of 45° and looking toward the south, located at Uozu City, Toyama Prefecture, Japan.

After 4 years of outdoor exposure, all the agricultural covering materials were recovered and measured for average light transmittance of visible rays having a wavelength range of 400-800 nm, by the use of a spectrophotometer. The results are shown in Table 1.

Table 1

Agricultural covering material	Thickness (μm)	Light transmittance (%)	
		Before exposure	After exposure
Film No. 2	60	91	85
Film No. 3	62	93	87
Film No. 1	60	93	87
Film No. 4	60	88	15
Soft vinyl chloride resin film	100	87	21
Polyester film	175	90	50
Polycarbonate resin panel	1,000	88	48
Acrylic resin panel	1,700	94	45

As is clear from Table 1, each of the soft vinyl chloride resin film, the polyester film, the polycarbonate resin panel, the acrylic resin panel (these are conventional covering materials), and the film No. 4 containing a large amount of an ultraviolet absorber gave 50% or less of a light transmittance after 4 years of outdoor exposure and became unusable as an agricultural covering material.

In contrast, the film Nos. 1-3 each comprising a fluororesin showed substantially no reduction in transparency after outdoor exposure and kept substantially the same transparency as before exposure.

2. Impact resistance

In order to evaluate the impact resistance of a sample film when hit by the wood pieces carried by a typhoon, a small stone having a weight of 300 g was dropped, from a height of 50 cm, on each of the film Nos. 2-3 and also on a flat glass (a product of Asahi Glass Co., Ltd., thickness: 3 mm) to examine the extent of the damage.

As a result, the flat glass was broken into fine pieces while the film Nos. 2-3 were not broken and had no damage.

From the above, it is presumed that a flat glass is easily broken by, for example, hail or the objects carried by typhoon and consequently the useful crops cultivated in a greenhouse covered with a flat glass receive deadly damage.

It was found out from the above tests that, of conventional agricultural covering materials, those satisfactory in transparency and impact resistance are only fluororesin films.

Examples of cultivation of useful crops

[1] Evaluation of cultivation of tomato

Each of the film Nos. 1-4 obtained in Examples of production of films was spread on a house (width: 10 m, depth: 20 m).

(1) Cultivation-1

Tomato seeds (variety: momotaro) were sown on Aug. 25 to raise seedlings. On Oct. 2, young seedlings in uniform growth in which 2-3 first clusters were in bloom, were set in each house so as to give an intrarow spacing of 50 cm.

The amounts of applied fertilizers are shown in Table 2. For about 10 days after setting, watering was made in a relatively small amount in such an extent that the young seedlings showed no wilting and made no rapid growth. The temperature of cultivation was controlled at 28°C in the morning, at 25°C in the afternoon and at 5°C or higher during the night. Therefore, hot-air heating was conducted with a heater during low-temperature seasons.

Table 2

Name of fertilizer	Amount of fertilizer applied (Kg/10 a)	Fertilizer components (Kg/10 a)			Remarks
		N	P	K	
Compound fertilizer for exclusive use in tomato	200	16	-	-	Initial manure
Magnesium-containing calcined phosphate	30	-	10.5	-	Initial manure
Fused phosphate fertilizer	40	-	8	-	Initial manure
Potassium sulfate	30	-	-	15	Initial manure
Sumika Ace	150	22.5	15	21	Additional manure
E No.2 (liquid fertilizer)	75	6	3	4.5	Additional manure

Harvesting was conducted from Dec. 10 through May 30, next year. The results of yield and other inspections are shown in Table 3.

The inspection items and the evaluation methods therefor are shown below.

Yield: an index when the total weight of the harvest obtained in the house covered with the film No. 4 was taken as 100.

The same calculation was made also in other cultivation examples.

Table 3

	Cultivation Example 1	Cultivation Example 2	Comparative Cultivation Example 1	Comparative Cultivation Example 2	Remarks
No. of spread film	2	3	1	4	
1. Yield	121	135	108	100	
2. Quality					
(1) Hardness of exodermis	Adequate	Adequate	Hard	Soft	
(2) Color of exodermis	Pink	Bright pink	Dark red	Light pink	
(3) Color of fruit inside	Pink	Pink	Orange with remaining dark green	Light pink	Jelly portion
3. Outbreak of diseases					
(1) Frequency of outbreak	Low	Low	Low	High	Gray mold
(2) Infectivity of diseases	Weak	Weak	Strong	Weak	
4. Vermination of injurious insects	Small amount	None	Large amount	None	Greenhouse whitefly

In the house covered with the film No. 1, the growth of tomato was slow; the stem and leaf and the fruit were hard; and the plant was small as a whole. Consequently, the timing of harvesting was later than in the houses covered with other films. Moreover, the balance between the color of the exodermis of fruit and the color of jelly portion inside fruit was not normal, and the color inside fruit was still green (unripe) but the color of exodermis was already ripe.

In the house covered with the film No. 4, the house inside became highly humid and the growth of the plant was too active, resulting in low yield. Moreover, the plant was soft as a whole and the colors of stem and leaf and fruit were light; this is presumed to be the reason for the high frequency of the outbreak of diseases.

(2) Cultivation-2

The cultivation management for next year was changed as follows based on the results of Cultivation-1, and cultivation (Cultivation-2) was conducted.

In the houses covered with the film Nos. 2-3, the same cultivation conditions as in Cultivation-1 were used.

In the house covered with the film No. 1, the amount of each fertilizer applied was increased by 10%; the total amount of water applied was increased by 10-15%; the night temperature was kept higher by 1°C; whenever direct sunlight was intense, a black cheese cloth capable of intercepting the light by 50% was spread at the ceiling.

In the house covered with the film No. 4, the amount of each fertilizer applied was decreased by 15%; the amount of water applied was decreased by about 20%; the night temperature was set lower by 1°C; and leaf picking was as necessary made so that the plant could receive sunlight as much as possible.

Thus, in the houses covered with the film No. 1 and 4, the time spent by farmer for operation was about 1.5-2 times those spent in the cases of the film Nos. 2-3. Particularly in the house covered with the film No. 1, the intensity of sunlight had to be checked as necessary, which disturbed other agricultural works. The results of cultivation are shown in Table 4.

Table 4

	Cultivation Example 3	Cultivation Example 4	Comparative Cultivation Example 3	Comparative Cultivation Example 4
No. of spread film	2	3	1	4
1. Yield	104	120	102	100
2. Quality				
(1) Hardness of exodermis	Adequate	Adequate	Slightly hard	Slightly soft
(2) Color of exodermis	Pink	Bright pink	Red	Light pink
(3) Color of fruit inside	Pink	Pink	Dark red	Light pink

As is clear from Table 4, in each of the houses covered with the film Nos. 1 and 4, the yield increased over the previous year and was about equal to that when the film No. 2 was used, but was lower than that when the film No. 3 was used. The plant qualities when the film No. 1 and 4 were used, were inferior to those when the film Nos. 2 and 3 were used.

As seen from the above results of 2-year cultivation, when the film Nos. 2-3 were used, cultivation of tomato was very easy as compared with when the conventional film Nos. 1 and 4 were used; there was no failure in cultivation; and a stable yield could be obtained.

Further, the harvested tomato had excellent quality, giving a very high profit.

[2] Example of cultivation of cucumber

Cucumber seeds (variety: Sharp One) were sown on Sept. 15 to raise seedlings. The seedlings were grafted to a stock (variety: King Tosa) on Sept. 22. The grafted seedlings were raised so as to give uniform growth. On Oct. 19, the young seedlings having 3.5 true leaves were set in each of the houses (width: 10 m, depth: 20 m) covered with the film Nos. 1-4, in a density of 4.8 plants/tsubo (3.3 m²).

The amount of each fertilizer applied is shown in Table 5. Until the number of nodes became 13-15, watering was kept as low as possible and the in-house temperature was controlled not to reach 25°C or higher. Thereafter, care was taken in order for the in-house minimum temperature not to become 11°C or lower.

Table 5

Name of fertilizer	Amount of fertilizer applied (kg/10 a)	Remarks
Compound fertilizer for cucumber	600	Initial manure
Fermented chicken droppings	600	Initial manure
Magnesium lime	80	Initial manure
Rice straw compost	2,000	Initial manure
E No. 2 (liquid fertilizer)	100	Additional manure
OKF-2	100	Additional manure

Harvesting was conducted from Nov. 20 through May 10, next year. The results of cultivation are shown in Table 6.

Table 6

	Cultivation Example 5	Cultivation Example 6	Comparative Cultivation Example 5	Comparative Cultivation Example 6	Remarks
No. of spread film	2	3	1	4	
1. Yield	125	133	98	100	
2. Quality					
Color of fruit	Green	Bright green	Dark green	Light green	
Hardness of fruit	Adequate	Adequate	Hard	Soft	
3. Condition of leaves					
Color	Green	Bright green	Dark green	Light green	
Sunscald	None	None	Seen	None	
Aging	None	None	Seen	None	Gray mold
4. Outbreak of diseases					
Frequency of outbreak	Low	Low	Low	High	
Infectivity of diseases	Weak	Weak	Strong	Weak	
5. Vermination of injurious insects	Small amount	None	Large amount	None	Greenhouse whitefly, aphid

As is clear from Table 6, in the house covered with the film No. 1, cucumber grew hard; the aging of leaves (that is, the leaves showed sunscald and reduced luster, then became blackish, and finally withered) was earlier by about 15-20 days than in the houses covered with other films; the plant vigour was weak; the growth was slower; and the timing of harvesting was later than in other houses.

In the house covered with the film No. 4, the humidity was higher than in the houses covered with other films and was incessantly high. Partly owing to this fact, the plant vigour was strong; the plant was weak as a whole; the growth was active; and the yield of fruit was not large.

Presumably owing to the weakness of whole plant, the damage by diseases, particularly the damage by gray mold was large.

In contrast, in the houses covered with the film Nos. 2-3, cultivation was possible with substantially no extra labor required; the yield was large; the plant quality was good; and the profitability was very high.

In the houses covered with the film Nos. 1 and 4, there were newly employed the same fertilizer amount, watering amount, temperature control and sunlight control as in the second year of tomato cultivation. As a result, the yields increased to about the same level as in the house covered with the film No. 2.

[3] Example of cultivation of melon

Melon seeds (variety: Andes) were sown on Jan. 15 to raise seedlings. On Feb. 10, the seedling having 2 true leaves were set in each of the houses shown in Table 7, in a density of 1,500 plants/tan (991 m²). Emerald sem was used as a stock and grafting was conducted by inarching.

Harvesting was conducted from May 20 through Jun. 15. The results of cultivation are shown in Table 7.

The melons harvested in the houses covered with the film Nos. 2-3, as compared with those harvested in the houses covered With the film Nos. 1 and 4, gave higher yields and higher qualities, could be marketed as high-quality products, and gave higher profitabilities.

Table 7

	Cultivation Example 7	Cultivation Example 8	Comparative Cultivation Example 7	Comparative Cultivation Example 8	Remarks
No. of spread film	2	3	1	4	
1. Condition of leaves					
(1) Color	Green	Bright green	Dark green	Light green	
(2) Sunscald	None	None	Seen	None	
2. Yield	116	121	103	100	
3. Quality					
(1) Saccharose content	13.9	14.1	13.3	13.5	
(2) Condition of net	Good	Good	Good	Coarse	
4. Outbreak of diseases					
(1) Frequency of outbreak	Low	Low	Low	High	Gray mold
(2) Infectivity of diseases	Weak	Weak	Strong	Weak	
5. Vermination of injurious insects	Small amount	None	Large amount	None	Greenhouse whitefly, aphid

[4] Example of cultivation of pimento

Pimento seeds (variety: Shin Sakigake No. 2) were sown on Jul. 30 to raise seedlings. The seedlings were sub-

jected to "kuntan" culture and set in each house on Aug. 30 in a density of 3.7 plants/tsubo (3.3 m²), and cultivation was continued. When the plant height became about 25 cm, four primary scaffold branches were erected and each connected to a plastic string hanged down from the top of the house. In this state, cultivation was further continued.

Harvesting was conducted from Nov. 15 through May end, next year. The results of cultivation are shown in Table

8.

Table 8

	Cultivation Example 9	Cultivation Example 10	Comparative Cultivation Example 9	Comparative Cultivation Example 10	Remarks
No. of spread film	2	3	1	4	
1. Yield	123	135	110	100	
2. Vermination of injurious insects	Small amount	None	Large amount	None	Yellow thrip

[5] Example of cultivation of watermelon

Watermelon seeds (variety: Shimao Max KE) were sown on Dec. 25 to raise seedlings. On Jan. 13, next year, the young seedlings were grafted to gourd (a stock) by cutting grafting. On Feb. 10, the grafted seedlings were set in the barks (bark-to-bark distance: 2m) of each of the houses shown in Table 9, in a density of 520 plants/tan (991 m²), and cultivation was continued. Harvesting was conducted from Apr. 25 through Jun. mid. The results of cultivation are shown in Table 9.

Table 9

	Cultivation Example 11	Cultivation Example 12	Comparative Cultivation Example 11	Comparative Cultivation Example 12	Remarks
No. of spread film	2	3	1	4	
1. Yield	118	125	98	100	
2. Quality					
Saccharose content	11.6	11.8	11.3	10.9	
3. Outbreak of diseases					
(1) Frequency of outbreak	Low	Low	High	Low	Gray mold, sclerofal disease
(2) Infectivity of diseases	Weak	Weak	Strong	Weak	
4. Vermination of injurious insects	Small amount	Small amount	Large amount	Small amount	aphid

[6] Examples of cultivation of celery and carrot

Celery seeds (variety: Cornel 619) were sown on Dec. 1 to raise seedlings. On Mar. 30, the seedlings were set in each of the houses shown in Table 10. Harvesting was conducted for 10 days starting from Jun. 20. The results of cultivation are shown in Table 10.

On Jan. 31, carrot seeds (variety: Kosei gosun) were sown in each of the houses shown in Table 11, to raise seedlings. On Feb. 20, the seedlings of delayed growth were removed for thinning so as to give an intrarow spacing of 20 cm, and cultivation was continued. Harvesting was conducted from May 10 through May 15. The results of cultivation are shown in Table 11.

Table 10

	Cultivation Example 13	Cultivation Example 14	Comparative Cultivation Example 13	Comparative Cultivation Example 14	Remarks
No. of spread film.	2	3	1	4	
1. Yield	118	122	81	100	
2. Quality					
(1) Color of whole plant	Green	Bright green	Excessively dark green	Light green	
(2) Hardness of whole plant	Adequate	Adequate	Too hard	Soft	
3. Outbreak of diseases					
(1) Frequency of outbreak	Low	None	High	High	Mainly sclerofal disease
(2) Infectivity of diseases	Weak	-	Strong	Weak	

Table 11

	Cultivation Example 15	Comparative Cultivation Example 15
No. of spread film	3	4
1. Yield	124	100
2. Quality		
(1) Color	Bright crimson	Crimson

[7] Example of cultivation of rose

On Dec. 20, rose seedlings (variety: Curl Red) were set in the house (width: 20 m, depth: 50 m) covered With the film No. 1 so as to give an intrarow spacing of 40 cm, and cultivation was conducted with the in-house temperature being kept at 16°C or higher. Harvesting was conducted from May 30 to Nov. 30. The results of cultivation are shown in Table 12.

In Table 12, yield refers to an index when the total number of the roses harvested in the house covered with the film No. 4 was taken as 100.

Table 12

	Cultivation Example 16	Cultivation Example 17	Comparative Cultivation Example 16	Comparative Cultivation Example 17	Comparative Cultivation Example 18
No. of spread film	2	3	1	4	1
1. Sunscald of leaves	Slight	None	Much	A little	Slight
2. Yield (number of harvested roses)	128	134	92	100	115
3. Quality					
(1) Flower color (petal)	Crimson	Bright crimson	Blackened (striped)	Light color (faint color)	Slightly blackened
4. Outbreak of diseases (gray mold)					
(1) Frequency of outbreak	None	None	Low	High	Low
(2) Infectivity of diseases	-	-	Strong	Weak	Strong
5. Vermination of injurious insects (aphid)	Small amount	None	Large amount	Large amount	None
Frequent use of cheese cloth	No	No	No	No	Yes

As is clear from Table 12, the roses cultivated in the house covered with the film No. 1 generated a large number of black striped stains in the petals and were not marketable.

To prevent the above phenomenon, a black cheese cloth capable of intercepting 50% of sunlight was spread at the ceiling of the house whenever sunlight was intense, whereby no intense sunlight was allowed to directly hit the roses.

As a result, the amount of the black stains generated was reduced to about 1/3. Meanwhile, when the cheese cloth was spread more frequently to decrease the amount of sunlight applied, the flower color of rose became light, causing a faint color phenomenon and giving lower quality.

In the house covered with the film No. 4, the flower color of rose became light and the roses harvested had a problem in commercial value. The high humidity in the house is presumed to have been one reason for the light flower color. It is presumed that, in a high humidity, the tree became soft and came to have reduced disease resistance and reduced injurious insect resistance. For prevention thereof, an agricultural chemical was spread, which gave stains owing to the agricultural chemical and an even lower commercial value.

In contrast, in the houses covered with the film Nos. 2-3, the flower color of rose was very bright crimson. Particularly, the roses cultivated in the house covered With the film No. 3 had a high commercial value.

As seen above, in the houses covered with the film Nos. 2-3, as compared with in the houses covered With the film Nos. 1 and 4, cultivation was very easy; there was no failure in cultivation by farmer and a stable yield was possible; moreover, high quality rose could be produced in a large amount; consequently, a high profit could be obtained.

[8] Examples of cultivation of prairie gentian and gerbera

Prairie gentian seeds (variety: Domino Pastel) were sown on Jul. 20 to raise seedlings. On Sept. 30, the young seedlings were set in each house, and cultivation was continued. Harvesting was conducted from Jan. 15 through Mar. 5.

The results of cultivation are shown in Table 13.

In Table 13, yield refers to an index when the total number of the prairie gentian harvested in the house covered with the film No. 4 was taken as 100.

Table 13

	Cultivation Example 18	Cultivation Example 19	Comparative Cultivation Example 19	Comparative Cultivation Example 20	Comparative Cultivation Example 21
No. of spread film	2	3	1	4	1
1. Yield (number of harvested plants)	124	135	89	100	118
2. Quality (1) Flower color	Crimson	Bright crimson	Blackened (striped)	Light color	Light crimson
Frequent use of cheese cloth	No	No	No	No	Yes

As is clear from Table 13, in the house covered with the film No. 1, the prairie gentian generated a large number of black stains in the petals and could not be marketable.

For prevention thereof, the same cheese cloth as used in Comparative Cultivation Example 18 was used in the

same manner as in Comparative Cultivation Example 18. As a result, frequent use of cheese cloth could diminish the black stains as in the flower of rose, but the flower color became light and the flower quality dropped.

In the house covered with the film No. 4, the flower color became light, posing a problem in commercial value.


In contrast, in the houses covered with the film Nos. 2 and 3, a large number of prairie gentian having a bright flower color could be harvested.

Results of cultivation similar to those of prairie gentian were obtained also in cultivation of gerbera (variety: Smoke World).

Claims

1. An agricultural covering material comprising a fluoro-resin film which intercepts the transmission of the ultraviolet rays having a wavelength range of at least 300-330 nm, by at least 40% and which transmits at least 70% of the visible rays having a wavelength range of 400-800 nm.
2. A covering material according to Claim 1, wherein the fluoro-resin film contains an inorganic fine powder capable of intercepting the transmission of the ultraviolet rays having a wavelength range of at least 300-330 nm.
3. A covering material according to Claim 1, wherein the fluoro-resin film has, on at least one side thereof, a coating layer containing an inorganic fine powder capable of intercepting the transmission of the ultraviolet rays having a wavelength range of at least 300-330 nm.
4. A covering material according to Claim 2 or 3, wherein the inorganic fine powder is titanium oxide, zinc oxide or a mixture thereof.
5. A covering material according to Claim 2, wherein the film contains 0.01-10% by weight of said inorganic fine powder.
6. A covering material according to Claim 3, wherein the coating layer contains 0.5-95% by weight of said inorganic fine powder.
7. A covering material according to Claim 1, wherein the fluoro-resin film is an ethylene / tetrafluoroethylene type copolymer obtained by copolymerizing ethylene, tetrafluoroethylene and, as necessary, 10 mole % or less of a C₄-C₁₂ perfluoroalkylvinyl monomer, the molar ratio of ethylene and tetrafluoroethylene being in the range of 40 / 60 to 60 / 40.
8. A greenhouse covered with a covering material of Claim 1.
9. A method for cultivation of useful crops, which comprises cultivating useful crops in a greenhouse covered with a covering material of Claim 1.

FIG. 1



INTERNATIONAL SEARCH REPORT

International application No.
PCT/JP94/00258

A. CLASSIFICATION OF SUBJECT MATTER		
Int. Cl ⁵ A01G13/02		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
Int. Cl ⁵ A01G13/02		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Jitsuyo Shinan Koho 1960 - 1994		
Kokai Jitsuyo Shinan Koho 1960 - 1994		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JP, A, 64-43535 (Nippon Carbide Industries Co., Inc.), February 15, 1989 (15. 02. 89), (Family: none) Fig. 1	1, 8, 9, 7
X	Claim 4	3-6
Y ₁	Claim 4, Fig. 1	
X	JP, A, 62-210925 (Mitsubishi Kasei Vineyl K.K.), September 17, 1987 (17. 09. 87), (Family: none) Fig. 1	1
Y ₂	JP, A, 4-133730 (Toppan Printing Co., Ltd.), May 7, 1992 (07. 05. 92), (Family: none) Claim 1	3-6
Y ₂	JP, A, 62-122545 (Sumitomo Chemical Co., Ltd.), June 3, 1987 (03. 06. 87), (Family: none) Claims 4, 5, 6, 7	3-6
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search March 16, 1994 (16. 03. 94)		Date of mailing of the international search report April 12, 1994 (12. 04. 94)
Name and mailing address of the ISA/ Japanese Patent Office Facsimile No.		Authorized officer Telephone No.

Form PCT/ISA/210 (second sheet) (July 1992)